

MARINE GEN SETS - 50Hz

Standard equipment included: Electrical wiring extension, oil extraction pump, rigid base, silent blocks, control panel with 4m harness, owner's and alternator manual.



Model	Maximum power		Phase	Dimensions	Dimensions
1500 RPM / 50 Hz				- cabinet	- no cabinet
7 GS/GSC	6.6 kW	6.6 kVA	1	892 x 560 x 608 mm	757 x 560 x 561 mm
8 GT/GTC	6.2 kW	7.8 kVA	3	892 x 560 x 608 mm	757 x 560 x 561 mm
10 GS/GSC	9.4 kW	9.4 kVA	1	1032 x 580 x 668 mm	885 x 580 x 609 mm
11 GT/GTC	8.4 kW	10.5 kVA	3	1032 x 580 x 668 mm	885 x 580 x 609 mm
14 GS/GSC	13.9 kW	13.9 kVA	1	1181 x 580 x 668 mm	1036 x 580 x 612 mm
17 GT/GTC	13.1 kW	16.4 kVA	3	1181 x 580 x 668 mm	1036 x 580 x 612 mm
20 GS/GSC	20.1 kW	20.1 kVA	1	1310 x 610 x 698 mm	1140 x 610 x 662 mm
25 GT/GTC	19.4 kW	24.3 kVA	3	1310 x 610 x 698 mm	1140 x 610 x 662 mm
29 GS/GSC	28.4 kW	28.4 kVA	1	1600 x 740 x 837 mm	1437 x 740 x 783 mm
35 GT/GTC	28 kW	35 kVA	3	1445 x 630 x 788 mm	1308 x 630 x 732 mm
45 GT/GTC	36 kW	45 kVA	3	1605 x 740 x 841 mm	1428 x 740 x 785 mm
50 GT/GTC	39.1 kW	48.9 kVA	3	1875 x 840 x 848 mm	1680 x 841 x 797 mm
68 GT/GTC	54.7 kW	68.4 kVA	3	1903 x 840 x 848 mm	1723 x 700 x 800 mm
85 GT/GTC	68 kW	85 kVA	3	2007 x 865 x 1048 mm	1779 x 866 x 969 mm
115 GT/GTC	90 kW	112.4 kVA	3	2007 x 865 x 1048 mm	1770 x 865 x 996 mm
165 GT/GTC	132 kW	165 kVA	3	2350 x 865 x 1146 mm	2079 x 804 x 1070 mm

3000 RPM / 50 Hz					
4 GSCH v3	3 kW	3 kVA	1	515 x 406 x 590 mm	NA

3000 RPM / 50 Hz - SPACE SAVER RANGE - NO CANOPY ONLY					
G-8M-3	8 kW	8 kVA	1	NA	845 x 482 x 568 mm
G-8T-3	6.4 kW	8 kVA	3	NA	845 x 482 x 568 mm
G-15M-3	15 kW	15 kVA	1	NA	1023 x 500 x 588 mm
G-15T-3	12 kW	15 kVA	3	NA	1022 x 485 x 548 mm
G-25M-3	25 kW	25 kVA	1	NA	1213 x 560 x 619 mm
G-25T-3	20 kW	25 kVA	3	NA	1213 x 560 x 619 mm

**3 year / 1000 hour
Warranty for Pleasure vessels**



**Brushless and
synchronous
Alternator**

Wet Exhaust standard

Full range of 60Hz models available

Many other accessories and options available -

Extra panel & harness
Includes 2nd Panel plus 12m harness.



Welcome kit
Includes oil, fuel & air filter, impeller, belt, oil, coolant, anode/s, fuse, paint, primer in a tool box.



Models available in different connections and operating voltages.

* Maximum power: power supplied at maximum capacity of the group. For more information see technical sheet. Technical specifications and presentation are subject to variations and changes without prior notice.